


Plug and play



Host control



4-to-1 split-screen display



Touch back control

WWW.EZCAST-PRO.COM

FOR ENTERPRISES

QuattroPod

Powered by EZCast Pro

A simple click, to cast secured wireless presentations

Authorized Distributor:



PT. MATA FACETS INTEGRA

Office Phone : 021-458-40387

Email : office@mfi.co.id

www.mfi.co.id




QuattroPod was awarded **Best Choice Award** during Computex



Wireless presentation as easy as plug and play

Share screens from your favorite smart device with plug and play. No app required.



Wireless Touch back control

Support touchscreen and wireless mouse



Host control to administer the pace of meetings







Control your meetings with QuattroPod to ensure staying on topic and making informed decision.



4-to-1 split-screen display to compare charts and graphs

Display up to 4 sources at the same time for better clarity in real-time information sharing. So you can see the full set of data to support decision making.

A Simple click, to cast secure wireless presentation

Product Name:	QuattroPod Mini	QuattroPod Starter	QuattroPod Standard	QuattroPod Deluxe	QuattroPod USB	QuattroPod Lite
Product Photo						
Key Features:						
Output resolution	4K					
Split screen up to 4	YES				NO	
Host control	YES				NO	
Touch back control	YES				NO	
Additional Features:						
Cast Code	YES				NO	
Interface:						
Transmitter	HDMI In /USB Type A male / USB Type A female	HDMI In /USB Type A male / USB Type A female	HDMI In / USB Type A male / USB Type A female / mini Display Port / Ethernet	HDMI In / USB Type A male / USB Type A female / mini Display Port / Ethernet	USB Type A male / USB Type C male / USB Type A female	HDMI In / Micro USB Type A female
Receiver	HDMI out (HDMI1.4) / USB Type A female / DC 5V					
HDCP	HDCP1.4					
Wi-Fi	802.11ac 1T1R, max. bandwidth 433Mbps (5GHz)					
Ethernet	10 / 100 / 1000M, supports PoE*					N/A
Power:						
Transmitter	DC 5V / 0.9A		DC 5V / 1A		DC 5V / 0.9A	
Receiver	DC 5V / 2A					
Power Consumption:						
Transmitter	Standby: 2W approx. Casting:4W approx.		Standby: 2W approx. Casting:5W approx.		Standby: 2W approx. Casting:4W approx.	
Receiver	Standby: 5W approx. Casting:10W approx.					
Working temp.	0~40°C					
Storage temp.	-20~70°C					
Dimensions:						
Transmitter	60x60x22 (mm)		80x80x26.5 (mm)		60x60x20 (mm)	
Receiver	80x120x25 (mm)		80x120x25 (mm)		80x120x25 (mm)	
					65x65x16 (mm) w/o antenna 80x120x25 (mm)	