



BEST Performance for Visualization

The Infinite™ deliver best performance on 55" video wall technology and remains simple in operation and easy to maintain. Suitable for use in Control Room, Meeting Room, Function Room and Digital Signage.

Industrial grade video wall for superior quality and durability, supporting business with 24x7 operation. With a 0.8mm true ultrathin bezel (bezet to bezel) it creates an infinite image on the video wall.

The Infinite comes with built a big picture processing allowing input content up to 4K, to be spread over multiple displays up to 10x10 for multi input content configuration, VW-5502 support all leading video wall processors including the ImagePath RealView™ series.

High Precision Video Wall Bracket (OPVB)

Unlike other brands ImagePath video wall will come with Original High Precision Video Wall Bracket (OPVB) designed and made by the ImagePath factory. OPVB allows each video wall display to be adjusted precisely up / down, forward / backward, and tilt. All of this makes installing ImagePath video wall fast, easy and precise. No need third party expensive video wall bracket to install videowall on the wall just need a horizontal pole to hang OPVB very quickly and easily.





PANEL

Screen Diagonal	55"
Backlight	LED
Resolution	1,920 x 1,080 (pixels)
Bezel to Bezel width	0.8 mm
Brightness (typ)/(min)	700 cd/m ² (typ.)
Contrast Ratio	1400 : 1 (typ.)
Response time	8 ms (typ.)
Pixel pitch	0,63 (H) mm x 0,63 (V) mm
Frequency	60 Hz
View angle	178° (H) / 178° (V)
Life time (typ)/(min)	60,000 hours (min.)
Color saturation (x% NTSC)	72%
Color support	1.07B colors
Usage (hour/day)	24/7
Big picture	Up to 10x10

INPUT/OUTPUT INTERFACE

HDMI	1
DVI	1
VGA	1
BNC	1
RS232-IN/OUT (RJ-45)	1/1

POWER

Voltage	100 V ~ 240 V, 50-60 Hz
Power consumption max	180W
Power consumption min	≤ 0.5W

WEIGHT & PACKING

Weight	26.3 Kg ± 1.5 Kg
Weight with packing	37.5 Kg ± 1.5 Kg
Packing size (W x D x H)	1415 * 300 * 895 mm

ENVIRONMENT

Operating temperature	0°C ~ 40°C
Storage temperature	-10°C ~ 60°C
Storage humidity	10% ~ 90% RH Non-Condensing
Operating humidity	20% ~ 85% RH Non-Condensing

ACCESSORIES

Video Wall Bracket (OPVB)	1 Set
Remote Controller	1
Power cord	1
User's manual	1
Warranty card	1

Dimension (mm):

